

Použití:

Určeny pro maskování vnějších i vnitřních čtyřhranných profilů před povrchovými úpravami, jako jsou práškové, katalytické barvy nebo galvanické pokovení.

OBDÉLNÍKOVÁ KRYTKA - skupina C



obj.číslo	rozměry vnitřní [mm]			rozměry vnější [mm]		
	a	b	c	x	y	z
B-0621-0000	4,0	0,7	20,0	7,8	3,0	22,0
B-0128-0000	4,4	0,8	6,6	8	3,0	8,6
B-0111-0000	6,0	0,8	11,0	7,8	3,0	13,0
B-0472-0000	8,0	6,0	12,0	12	10,0	19,0
B-0316-0000	9,6	4,6	8,0	11,6	6,6	9,0
B-1090-0000	10,0	1,0	12,0	12	3,0	13,0
B-0317-0000	12,2	4,6	8,0	14,2	6,6	9,0
B-0634-0000	13,0	1,0	50,0	17	5,0	52,0
B-0635-0000	14,0	2,8	50,0	18	7,0	52,0
B-0782-0001	17,0	17,0	7,0	22	22,0	8,0
B-0144-0000	17,3	4,6	10,0	20	8,0	12,4
B-0244-0001	19,0	16,5	7,0	30	24,0	9,0
B-1218-0000	20,0	6,0	50,0	22,5	9,0	54,0
B-0960-0000	20,5	5,0	11,0	25	9,0	14,0
B-0782-0000	20,5	20,5	6,5	22,5	22,5	8,0
B-0150-0000	24,5	4,3	6,4	28	5,9	7,7
B-1219-0000	25,0	6,0	50,0	27,5	9,0	54,0
B-0965-0000	25,3	7,2	6,0	29,3	8,2	7,5
B-0992-0000	25,6	12,8	26,0	31	17,0	28,0
B-1058-0000	29,6	5,8	30,0	35,3	11,8	32,4
B-1225-0000	30,0	8,0	12,0	32,2	10,0	13,0
B-1904-0000	32,2	3,0	1,4	34,2	4,2	2,5

TECHNICAL SILICONE PARTS

SILROC CZ
the world of silicone

SKUPINA C - OBDÉLNÍKOVÉ KRYTKY

www.silroc.cz



OBDÉLNÍKOVÁ KRYTKA - skupina C

obj. číslo	rozměry vnitřní [mm]			rozměry vnější [mm]		
	a	b	c	x	y	z
B-1903-0000	36,0	4,0	1,4	37,6	5,6	2,5
B-1183-0000	40,0	12,0	16,0	44	16,0	18,0
B-0549-0000	70,0	8,1	17,0	73	11,0	18,5
B-2596-0000	78,0	6,0	7,0	81	9,0	8,0
B-0544-0000	88,0	4,8	7,5	90,4	7,2	8,5
B-0140-0000	90,0	11,0	13,0	95	15,0	15,4
B-0141-0000	105,0	11,0	13,0	110	15,0	15,4